

INSTANT STARTING POWER FOR EVERYDAY CARS

The RB 1500 booster delivers instant starting power for regularpetrol and diesel cars– as well as motorcycles, ATVs and other powersport vehicles. Compact and glove-box friendly, it's sized to live with your car. Spark-proof technology, reverse-polarity protection, USB charging ports and a built-in flashlight – always ready when you need it.

SIZED FOR YOUR DAILY DRIVE AND SECOND CARS

Meet the RB 1500 portable booster – compact, lightweight and built for regularpetrol and diesel cars – as well as motorcycles, ATVs and other powersport vehicles. With 1500A battery peak current and up to 20 starts on a single charge, it delivers instant starting power. Spark-proof technology and reverse-polarity protection ensure confident operation every time. Beyond jump-starting, the RB 1500 works as a handy power bank with USB-A and USB-C ports for charging your devices. A built-in LED flashlight with three lighting modes adds extra versatility. Designed by Sweden's charging pioneers CTEK, it's the everyday essential that stays with your car

GLOVE BOX-READY, ALWAYS THERE

The RB 1500 delivers instant starting power for drivers of regular everyday cars – as well as motorcycles, ATVs and other powersport vehicles. Whether you're dealing with an unexpected flat battery or need to charge your phone on the go, it's always ready. The everyday essential that lives with your car, not in the garage.

- Instant starting power for regular cars,– as well as motorcycles, ATVs and other powersport vehicles
- Jump-starts 12V lead-acid batteries, including AGM, EFB, WET, GEL and Ca/Ca
- Spark-proof technology and reverse polarity protection for safe use.
- Compact design – fits easily in your glove box or door pocket.
- USB power bank plus a built-in flashlight with 3 lighting modes.
- Up to 20 starts on a single charge – always ready when you need it.
- Quality Swedish-inspired design for dependable everyday performance.
- Charges phones, tablets and other electronics through built-in USB-A and USB-C ports.
- Comes with clamps, soft storage bag and user guide.
- Ergonomic design with intuitive LED indicators.
- 2-year warranty.

CTEK





TECHNICAL DATA

BATTERY PEAK CURRENT	1500A / 20 Starts
PEAK CURRENT	1100 A (0,1 s), 1500 A (0,01 s)
START CURRENT	450A (1 sec), 230 A (5 sec)
INTERNAL BATTERY CAPACITY	2000 mAh, 14,8 V, 29,6 Wh
FAST CHARGING TIME	1.5 hours
INTERNAL BATTERY PACK TYPE	4S1P
INTERNAL BATTERY CELL CHEMISTRY	Lithium Manganese Nickel and Cobalt
INTERNAL BATTERY CHARGE TEMPERATURE	0 ˚C to +45 ˚C (32 °F to +113 °F)
INTERNAL BATTERY DISCHARGE TEMPERATURE	-20 ˚C to +55 ˚C (-4 °F to +131 °F)
INPUT	PD30W (5V 3A; 9V 3A; 12V 2.5A; | 15V 2A; 20V 1.5A)
OUTPUT	Quick charge (5V 3A; 9V 2A; | 12V 1.5A) PD30W (5V 3A; 9V 3A; | 12V 2.5A; 15V 2A; 20V 1.5A) | 12V jump starter
BATTERY TYPES	12 V: WET, MF, Ca/Ca, AGM, EFB, GEL
BATTERY CHEMISTRY	Lead acid
START VOLTAGE	2.5 V
AMBIENT OPERATING TEMPERATURE	-20 °C to +55 °C (-4 °F to +131 °F)
AMBIENT STORAGE TEMPERATURE	-20 °C to +50 °C (-4 °F to +122 °F)
USER INTERFACE	Display
DIMENSIONS (L X W X H)	198 x 93 x 36 mm (7.80 × 3.66 × 1.42 in)
NET WEIGHT (UNIT WITH CABLES)	742 g (1.64 lb)
DEGREE OF PROTECTION	IP54
DETACHABLE STARTING CABLE LENGTH OUTPUT	0.25 m (9.84 in)
COOLING	Natural convection
MAINS ADAPTER CABLE LENGTH	1 m (39.37 in)
MAINS ADAPTER CABLE TYPE	USB-C
WARRANTY	2 years

GUARANTEED QUALITY WITH CTEK

CTEK customer support is available to answer any questions related to charging and CTEK chargers. Safety, simplicity and flexibility characterizes all products and solutions developed and sold by CTEK. CTEK supply chargers to more than 70 countries throughout the world. CTEK is also a reliable OEM supplier to many of the world's most prestigious car and motorcycle manufacturers.

For more information visit WWW.CTEK.COM

© CTEK SWEDEN AB, 2025 | EN

All products and product specifications are subject to change without notice, to improve reliability, function or design. In the event of product error, we reserve the right to inspect the product and verify the fault. All product returns are subject to our standard warranty terms.

CTEK