

RB 2000

INSTANT STARTING POWER FOR THE EVERYDAY FAMILY CAR

The RB 2000 booster provides instant starting power for hatchbacks, saloons, estates, compact SUVs and smaller diesels. Versatile and portable, it's the everyday answer for everyday cars. With up to 25 starts on a single charge, spark-proof technology, reverse-polarity protection, USB charging ports and a built-in flashlight it delivers dependable power for the vehicles most families drive.

COMPACT BOOSTER FOR EVERYDAY FAMILY VEHICLES

Say hello to the RB 2000 portable booster – versatile, capable and built for the vehicles most families drive. With 2000A battery peak current and 300A starting current, it jump-starts hatchbacks, saloons, estates, compact SUVs and smaller diesels with ease. Advanced safety features, including spark-proof technology and reverse polarity protection, ensure confident operation every time. Beyond jump-starting, the RB 2000 works as a handy power bank with USB-A and USB-C ports for charging your devices. A built-in LED flashlight with three lighting modes adds extra versatility. Designed by Sweden's charging pioneers CTEK, it's the everyday answer for everyday cars.

JUMP-START YOUR DAILY DRIVE

The RB 2000 delivers dependable jump-starting power for drivers of everyday family vehicles. Whether you're dealing with a flat battery in your hatchback, saloon or compact SUV, it's always ready – with up to 25 starts on a single charge. The power your car needs, and nothing you'll never use – that's the RB 2000.

- Instant starting power for hatchbacks, saloons, estates, compact SUVs and smaller diesels.
- Jump-starts 12V lead-acid batteries, including AGM, EFB, WET, GEL and Ca/Ca
- Spark-proof technology and reverse polarity protection for safe use.
- Compact design – capable power that fits in the glove compartment.
- USB power bank plus a built-in flashlight with 3 lighting modes.
- Up to 25 starts on a single charge – always ready when you need it.
- Quality Swedish-inspired design for dependable everyday performance.
- Charges phones, tablets and other electronics through built-in USB-A and USB-C ports.
- Comes with clamps, soft storage bag and user guide.
- Ergonomic design with intuitive LED indicators.
- 2-year warranty.

CTEK





TECHNICAL DATA

BATTERY PEAK CURRENT	2000A / 25 Starts
PEAK CURRENT	1200A (0.1 sec), 1800 A (0.01 sec)
START CURRENT	650A (1 sec), 300A (5 sec)
INTERNAL BATTERY CAPACITY	2500 mAh, 14,8 V, 37 Wh
FAST CHARGING TIME	2 hours
INTERNAL BATTERY PACK TYPE	4S1P
INTERNAL BATTERY CELL CHEMISTRY	Lithium Manganese Nickel and Cobalt
INTERNAL BATTERY CHARGE TEMPERATURE	0 ˚C to +45 ˚C (32 °F to +113 °F)
INTERNAL BATTERY DISCHARGE TEMPERATURE	-20 ˚C to +55 ˚C (-4 °F to +131 °F)
INPUT	PD30W (5V 3A; 9V 3A; 12V 2.5A; | 15V 2A; 20V 1.5A)
OUTPUT	Quick charge (5V 3A; 9V 2A; | 12V 1.5A) PD30W (5V 3A; 9V 3A; | 12V 2.5A; 15V 2A; 20V 1.5A) | 12V jump starter
BATTERY TYPES	12 V: WET, MF, Ca/Ca, AGM, EFB, GEL
BATTERY CHEMISTRY	Lead acid
START VOLTAGE	2.5 V
AMBIENT OPERATING TEMPERATURE	-20 °C to +55 °C (-4 °F to +131 °F)
AMBIENT STORAGE TEMPERATURE	-20 °C to +50 °C (-4 °F to +122 °F)
USER INTERFACE	Display
DIMENSIONS (L X W X H)	198 x 93 x 36 mm (7.80 × 3.66 × 1.42 in)
NET WEIGHT (UNIT WITH CABLES)	783 g (1.73 lb)
DEGREE OF PROTECTION	IP54
DETACHABLE STARTING CABLE LENGTH OUTPUT	0.25 m (9.84 in)
COOLING	Natural convection
MAINS ADAPTER CABLE LENGTH	1 m (39.37 in)
MAINS ADAPTER CABLE TYPE	USB-C
WARRANTY	2 years

GUARANTEED QUALITY WITH CTEK

CTEK customer support is available to answer any questions related to charging and CTEK chargers. Safety, simplicity and flexibility characterizes all products and solutions developed and sold by CTEK. CTEK supply chargers to more than 70 countries throughout the world. CTEK is also a reliable OEM supplier to many of the world's most prestigious car and motorcycle manufacturers.

For more information visit WWW.CTEK.COM

© CTEK SWEDEN AB, 2025 | EN

All products and product specifications are subject to change without notice, to improve reliability, function or design. In the event of product error, we reserve the right to inspect the product and verify the fault. All product returns are subject to our standard warranty terms.

CTEK