

## SYSTEM MONITOR 200A



### SUITABLE FOR USE WITH D250SE, SMARTPASS 120S, I1225 & M25

The unit continually monitors the voltage, the current (charge and discharge) and calculates the state of charge together with the time remaining to charge or discharge the battery.

### CTEK SYSTEM MONITOR 200A

Included in the package is a 5m cable from display to battery, with ring terminals for shunt, fuse holder and M8 ring terminal to battery.

- Stage of charge in %
- Battery voltage
- Charge and discharge current
- Estimated charge and discharge time remaining



### TECHNICAL DATA

ARTICLE NUMBER	40-484
BATTERY CHEMISTRY	Lead acid
SUPPLY VOLTAGE	8-16 VDC
SUPPLY CURRENT	1.5 mA
BATTERY CAPACITY	5-999 Ah
LOAD CURRENT	199 A Max
CHARGE CURRENT	199 A Max
SHUNT STANDARD	50 mV @ 100 A
DIMENSIONS (L X W X H)	125 x 62 x 23 mm
WARRANTY	2 years

All products and product specifications are subject to change without notice, to improve reliability, function or design. In the event of product error, we reserve the right to inspect the product and verify the fault. All product returns are subject to our standard warranty terms.

**CTEK**