

CHARGING SOLUTION FOR DEALERSHIP SHOWROOMS OR FAIRS

Knowing when a vehicle battery in the showroom needs a charge and being able to deal with it simply and quickly, is vital in helping dealerships to deliver a first-class experience to the customer, right from the moment they step into the showroom.

The MXS10 CIC is a battery management system that will help to monitor and maintain vehicle batteries in the showroom. It consists of two highly effective and simple to use pieces of equipment: A simple 'traffic light' Comfort Indicator allows dealership staff to easily monitor battery status and identify if the battery needs a charge. A CTEK MXS10 battery charger delivers a 10A charge safely, and without the need to remove the battery from the vehicle.

The unique CTEK Comfort Connect system allows the charger to be connected to the battery via the Comfort Indicator, enabling showroom staff to safely, simply and quickly deliver a charge without assistance from a technician. By taking a pro-active approach to battery management and using the MXS10 CIC system, battery related problems in the showroom can be eliminated, maximizing the customer experience and protecting dealership and brand reputation.

PRACTICAL AND SIMPLE TO USE

The MXS 10 charger is a practical and simple to use charger with an easy to understand display, It is non-sparking, reverse polarity protected and short-circuit proof, and comes with a 2 year warranty.

- Maintains larger batteries up to 300Ah
- Easy to read LED display
- Comes with Connect - Eyelet and Connect - Clamp connectors
- Splash and dust proof (IP65)
- Safe spark free operation
- Reverse polarity protected
- Short circuit proof
- Fully automatic 'connect and forget' 8 step charging
- Charges batteries from 20-200Ah
- Temperature sensor, AGM and Recond programs
- Power supply for 12V equipment
- 2-year warranty

MXS 10 CIC



TECHNICAL DATA

INPUT	220-240 VAC, 50-60 Hz, 1.4 A
OUTPUT	14.4/14.7/15.8/13.6 V, 10 A
CHARGER TYPE	8 step, fully automatic charging cycle
BATTERY TYPES	12 V: WET, MF, Ca/Ca, AGM, GEL
BATTERY CAPACITY	20-300 Ah
START VOLTAGE	2.0 V
BACK CURRENT DRAIN*	Corresponding to less than 1 Ah/month
POWER SOURCE	220 V -> 12 V
BATTERY VOLTAGE	12 V
AMBIENT OPERATING TEMPERATURE	-20 °C to +50 °C
TEMPERATURE COMPENSATION	External charge voltage temperature compensation sensor
BATTERY CHEMISTRY	Lead acid
DEGREE OF PROTECTION	IP65
WARRANTY	2 years

*) Back current drain is the current that drains the battery if the charger is not connected to the mains. CTEK chargers have a very low back current.

GUARANTEED QUALITY WITH CTEK

CTEK customer support is available to answer any questions related to charging and CTEK chargers. Safety, simplicity and flexibility characterizes all products and solutions developed and sold by CTEK. CTEK supply chargers to more than 70 countries throughout the world. CTEK is also a reliable OEM supplier to many of the world's most prestigious car and motorcycle manufacturers.

For more information visit WWW.CTEK.COM



All products and product specifications are subject to change without notice, to improve reliability, function or design. In the event of product error, we reserve the right to inspect the product and verify the fault. All product returns are subject to our standard warranty terms.

CTEK